AD-C Series | Passive Ceiling Speaker











AD-C4T | **AD-C4T-LP** | **AD-C6T** | **AD-C6T-LP**

AD-C4T
2-way Passive Ceiling Speaker
4.5”, 30W

AD-C4T-LP
2-way Passive Ceiling Speaker
4.5”, 30W, shallow can

AD-C6T
2-way Passive Ceiling Speaker
6.5”, 60W

AD-C6T-LP
2-way Passive Ceiling Speaker
6.5”, 60W, shallow can

전 객석에 평탄한 주파수 커버리지를 제공하는 DMT™ 기능
Q-SYS 및 CXD Seires 앰프를 활용하여 Intrinsic Correction™ (DSP 내장) 기능 활용
16Ω 운용 겸용의 70/100V 멀티탭 트랜스포머스 위치 장착

	AD-C4T	AD-C4T-LP	AD-C6T	AD-C6T-LP
Frequency Range (-10dB)	68Hz–20kHz	60Hz–20kHz	63Hz–20kHz	65Hz–20kHz
Nominal Coverage	150° conical DMT	150° conical DMT	135° conical DMT	135° conical DMT
Output (Peak SPL@1M)	108dB	108dB	112dB	112dB
Rated noise power	30 W	30 W	60 W	60 W
Sensitivity (1W@1m)	87 dB	87.5 dB	88 dB	88 dB
LF Driver	4.5in (114mm) weather resistant paper cone woofer		6.5in (152mm) weather resistant paper cone woofer	
HF Driver	0.75in (19mm) aluminum dome tweeter		0.75in (19mm) aluminum dome tweeter	
Transformer Taps	70V: 30,15,7.5,3.75W and 16 bypass 100V: 30,15,7.5W and 16 bypass		70V: 60,30,15,7.5W and 16 bypass 100V: 60,30,15W and 16 bypass	
Dimensions (Ø x H)	Ø 280 x 100mm	Ø 230 x 176mm	Ø 280 x 237mm	Ø 340 x 100mm
Net Weight	3kg	2.9kg	4.3kg	4.2kg
타공사이즈	Ø 245mm	Ø 195mm	Ø 245mm	Ø 305mm
Impedance	16 ohms	16 ohms	16 ohms	16 ohms