



AD-S10T
2-way Passive Loudspeaker, 10", 250W

G2B No. **22760502**

AD-S12
2-way Passive Loudspeaker, 12", 300W

G2B No. **22760501**

AD-S112sw
Passive Subwoofer, 12", 300W

- IP54 방수/방진 등급
- 전 객석에 평탄한 주파수 커버리지를 제공하는 DMT™ 기능
- 특허인 X-Mount 기술로 스피커를 쉽게 설치하고, 시간이 흐르면서 미끄러지는 일이 없도록 다양한 각도로 배치 가능

	AD-S10T	AD-S12	AD-S112sw
Effective frequency range	50 - 19kHz	52 – 20kHz	30 - 135 Hz
Rated noise power / voltage	250W / 45V (rms)	300W / 50V (rms)	300W / 50V (rms)
Rated Sensitivity	92dB, 1W@1m	95dB, 1W@1m	90dB, 1W@1m
Coverage angle (-6 dB)	90° Conical DMT	75° Conical DMT	
Maximum peak SPL	122dB	126dB	121dB
Rated impedance	8Ω	8Ω	8Ω
Transformer Taps (70 V)	100, 50, 25, 12.5W and 8Ω Bypass		
Transformer Taps (100 V)	100, 50, 25W and 8Ω Bypass		
HF transducer	1″ exit / 1.4″ voice-coil compression driver	1″ exit / 1.4″ voice-coil compression driver	
LF transducer	10″ Weather Resistant Paper Cone Woofer, 2.5″ / 64mm Voice-coil	12″ Weather Resistant Paper Cone Woofer, 3″ / 76mm Voice-coil	12″ weather resistant paper cone woofer, 2.5″ / 64 mm voice coil
Dimensions (H x W x D)	516 x 318 x 298mm	594 x 354 x 323mm	594 x 354 x 323mm
Net Weight	15kg	16kg	13.2 kg



M10 Kit-C
M10 forged-shoulder steel eyebolt kit