AD-S Series | Passive Loudspeaker



AD-S4T
2-way Passive Loudspeaker, 4.5", 50W

AD-S6T
2-way Passive Loudspeaker, 6.5", 150W

AD-S8T
2-way Passive Loudspeaker, 8", 200W

G2B No. **22760503**

- IP54 방수/방진 등급
- 전 객석에 평탄한 주파수 커버리지를 제공하는 DMT™ 기능
- 특허인 X-Mount 기술로 스피커를 쉽게 설치하고, 시간이 흐르면서 미끄러지는 일이 없도록 다양한 각도로 배치 가능

	AD-S4T	AD-S6T	AD-S8T
Effective frequency range	68 Hz – 20 kHz	60 Hz – 20 kHz	55 Hz – 20 kHz
Rated noise power / voltage	50W / 20V (rms)	150W / 35V (rms)	200W / 40V (rms)
Rated Sensitivity	87dB, 1W@1m	89dB, 1W@1m	90dB, 1W@1m
Coverage angle (-6 dB)	120° Conical DMT	105° Conical DMT	105° Conical DMT
Maximum peak SPL	110dB	116dB	119dB
Rated impedance	8Ω	8Ω	8Ω
Transformer Taps (70 V)	30, 15, 7.5, 3.75 watts and 8Ω bypass	60, 30, 15, 7.5 watts and 8Ω bypass	60, 30, 15, 7.5 watts and 8Ω bypass
Transformer Taps (100 V)	30, 15, 7.5 watts and 8Ω bypass	60, 30, 15 watts and 8Ω bypass	60, 30, 15 watts and 8Ω bypass
HF transducer	0.75" silk dome tweeter / 0.75" voice-coil	1" silk dome tweeter / 1" voice-coil horn loaded	1″ exit / 1.4″ voice-coil compression driver
LF transducer	4.5" weather treated paper cone woofer, 1"/ 25mm voice-coil	6.5" weather resistant paper cone woofer, 1.5" / 38mm voice-coil	8" weather resistant paper cone woofer, 2.0" / 50mm voice-coil
Dimensions (H x W x D)	261 x 161 x 163mm	365 x 215 x 215mm	440 x 254 x 251mm
Net Weight	2.9 kg	6.2 kg	11kg

Accessories



Yoke Mount
(AD-S8T, AD-S10T, AD-S12)



X-Mount