

**AP-4122m****AP-5122m****AP-212sw****AP-4122m**

2-way Passive Stage Monitor  
Speaker, 12", 325W

**AP-5122m**

2-way Passive Stage Monitor  
Speaker, 12", 550W

**G2B No. 22757356**

**AP-212sw**

Passive Subwoofer,  
Dual 12" 600W

- 전 객석에 평탄한 주파수 커버리지를 제공하는 DMT™ 기능
- 세련된 디자인의 인클로저
- 높은 출력이 요구되는 다양한 설치환경에 적합한 Speaker

55Hz - 20kHz	55Hz - 18kHz
325W / 36V rms	550W / 60V rms
96dB, 1W @ 1m	95dB, 1W@1m
90° Conical DMT	90° Axisymmetric
121dB@1m, continuous	122dB@1m, continuous
127dB@1m, peak	128dB@1m, peak
4Ω	8Ω
45 mm (1.75-inch) voice coil, compression driver	76 mm (3-inch) voice coil, compression driver; 72 W / 24 V (2 hours)
305mm (12-inch) driver with 64mm (2.5-inch) voice coil	305mm (12-inch) driver with 102mm (4-inch) VC; 450W / 60V (2Hsr)
510 x 385 x 370 mm	660 x 381 x 330mm
18.1 kg	29.5kg

Frequency Range at (-10 dB)	35Hz – 250Hz
Rated Noise Power / Voltage	600W / 49V rms
System Sensitivity	93dB
Maximum Rated SPL (Passive)	122 dB continuous 128 dB peak
Rated Impedance	4Ω
LF Transducer	2x 305mm (12-inch) weather resistant cone woofer, 64mm (2.5-inch) voice coil
Dimensions (H x W x D)	660 x 381 x 610mm
Net Weight	30.4kg

**Subwoofer Caster Kit (AP-212sw)**

**Speaker Pole M2035-36 (Horizontal) (AP-212sw)**

**Speaker Pole M2035-26 (Vertical) (AP-212sw)**