





E110 2-way Passive Loud & Stage Monitor Speaker, 10", 300W **E12** 

2-way Passive Loud & Stage Monitor Speaker, 12", 400W

G2B No. **23210852** 

**E15** 

2-way Passive Loud & Stage Monitor Speaker, 15", 500W

G2B No. 23210853

- E Series Entertainment System : 고급 디지털 시그널 프로세싱 튜닝과 QSC의 GXD,PLD 앰프 또는 TouchMix 디지털 믹서의 옵션 사용
- 전 객석에 평탄한 주파수 커버리지를 제공하는 DMT™ 기능
- 영구 설치 가능한 U 스타일의 요크와 M8 리깅 키트 사용 가능

Frequency Range (-10 dB)	50 Hz - 20 kHz	46Hz - 20kHz	43Hz - 20kHz
Power capacity	continuous/peak : 300W / 1200W	Continuous/Peak : 400W / 1600W	Continuous/Peak : 500W / 2000W
Sensitivity	95dB, 1W @ 1m	96dB, 1W @ 1m	97 dB, 1W @ 1m
Coverage Angle	85° conical DMT	85° conical DMT	75° conical DMT
Output (Peak SPL @ 1m)	126dB	128dB	130dB
LF Drivers	254mm (10") driver with 64mm (2.5")	305mm (12") driver with 76mm (3")	381mm (15") driver with 89mm (3.5")
	voice coil	voice coil	voice coil
HF Drivers	25mm (1") exit, 45mm (1.75") voice coil,	25mm (1") exit, 45mm (1.75") voice coil,	38mm (1.5") exit, 71mm (2.8")
	compression driver	compression driver	voice coil, compression driver
Nominal Impedance	8Ω	8Ω	8Ω
Net weight	20kg	23kg	31kg
Dimensions (W x H x D)	330 x 560 x 330mm	360 x 616 x 371mm	420 x 716 x 445mm

## Accessories







COVER

YOKE MOUNT

M8 EYEBOLT KIT-A