



WL218-sw



GP118-sw



GP218-sw

	WL218-sw Passive Subwoofer (Flying), DUAL 18", 1700W	GP118-sw Passive Subwoofer (Stack), 18", 850W	GP218-sw Passive Subwoofer (Stack), DUAL 18", 1700W
	• 10:1 design factor를 통해서 8개 이상의 WL218–sw 서브 우퍼 지원 • 4"의 섬유유리 보이스코일과 견고한 구조 • Long–excusrion을 갖고 있는 최고급 고출력 우퍼		
Driver Information LF	Dual 18″ transducers, 4″ voice coil, ceramic magnet assembly	18″ transducers, 4″ voice coil, ferrite magnet	Dual 18″ transducers, 4″ voice coil, ceramic magnet assembly
Nominal Impedance	4 ohms	8 ohms	4 ohms
Power Handling	1700W	850 W	1700W
Sensitivity (1 W at 1 m)	101 dB	98 dB	101.5 dB
Frequency Range (-10dB)	31Hz – 1kHz (without processing)	29 Hz - 800 Hz (without processing)	27.4Hz - 1.2kHz (without processing)
Peak Output	139dB	135dB	140.5dB
Dimensions (H x W x D)	541 x 1166 x 882mm	531 x 656 x 772mm	508 x 1198 x 762mm
Net Weight	92.5kg	50.3kg	86.6kg



CP-218-0
Wood Caster Pallet
(GP-218-sw)



CVR-GP218 Soft Cover **(GP218)**
CVR-GP218 Padded transport cover
(GP-218)

CP-218-1 Wood Caster Pallet **(GP-218-sw)**
WL SMALL GRID Steel grid **(WL2102 / WL2102-w)**
WL LARGE GRID Steel grid **(WL2102 / WL2102-w)**
WL-CASE ISIS WideLine transport/storage case