

Earthworks, Inc.

37 Wilton Road, Milford, NH, 03055

Phone: (603) 654 - 2433 ext. 114 Fax: (603) 654 - 6107 Email: info@earthworksaudio.com



WL40V

Wireless Vocal Microphone Capsule

User's Manual






Brief Description


The WL40V has been engineered in wireless capsule form from the SR40V Handheld Vocal Microphone. Designed to maintain the same signature sound as its wired counterpart, the WL40V delivers a detailed and realistic vocal sound that requires little to no EQ. Its near textbook perfect hypercardioid polar pattern and extended flat frequency response translate to a natural on and off-axis performance coupled with benchmark levels of clarity and detail. The WL40V Wireless Vocal Microphone Capsule head is interchangeable with any screw-on-type handheld transmitters that receive a 31.3mm/pitch 1.0mm threading (1.25" / 28 thread pitch).

Key Features:

- clean and open sound reproduction
- · free of coloration
- · warm, not boomy, when used up close
- · uniform response across all frequencies

Frequency Range and Polar Pattern





WL40V Technical Specifications

Frequency Response: 50Hz to 40kHz Polar Pattern: Hypercardioid Sensitivity: 3mV/Pa Power Requirements: 5-12V @ 500μA using center & outer ring Max Acoustic Input: 136dB SPL Distortion: Less than 3% THD Output Impedance: 300Ω, unbalanced (center & outer ring) Noise: 22dB SPL, A weighted Threads: 1.25″/28 thread pitch; 31.3mm/pitch 1mm threading Dimensions LxD: 3.7 in (93.98mm) x 1.93 in (49mm) max diameter & 1.46 in (37mm) min diameter Weight: 0.2 lbs (90g)

Warranty & Registration

If you have any problems with your Earthworks products, please contact our Repair Department by email at repairs@earthworksaudio.com or by telephone at (603) 654-6247, ext 119.

To help you get the most out of your Earthworks purchase, please take a moment and register your product with us online at **earthworksaudio.com/register**.